

Quick Check® 890 Bar Code Verifier



Overview

From the global leader in Verification comes the Quick Check® 890 Verification System – the newest addition to the well-known and respected Quick Check family of products.

The first in a new class of Quick Check Linear Verifiers, the QC890 product was built to deliver world-class performance for a broad range of market applications.

Featuring the ultimate balance of performance, durability, ergonomics, and connectivity solutions, the QC890 delivers years of dependable linear bar code verification for applications in the retail supply chain, healthcare, transportation, and industrial markets.

The first linear bar code verifier to earn the Adaptus™ Imaging Technology brand, the new QC890 is powered by Adaptus Imaging 5.0, delivering break-through linear imaging performance and versatility. Advanced signal processing improves performance & accuracy needed for ISO Verification measurements.

Reliable, out-of-box solution coupled with flexible configurations makes the QC890 the ideal choice for customers who appreciate best-in-class value in a verifier.

To learn more about how the QC890 can work for you, contact us at any of the locations listed on the back or visit us at [www](http://www.handheld.com).

The QC890 Advantage

Premium Features

Performance and Versatility Powered by Adaptus™ Imaging Technology 5.0

Advanced signal processing improves accuracy needed for ISO verification measurements.

Out-of-the Box Solution

Single device delivers excellent performance across the broadest range of customer applications.

- Ability to choose Operating Systems from a selection of Microsoft® Windows®, Windows® Mobile for Pocket PC, and Mac OS®
- Battery operated by a rechargeable battery for full portable operation
- Multiple language support – English, Japanese, Chinese
- Flexibility through multiple interfaces: RS-232, USB, or Bluetooth® wireless

Design

Sleek, modern industrial design results in a device for increased operator comfort and productivity.

- Unique alignment window provides quick and easy test sample positioning
- Push button hands-free operation increases repeatability in challenging applications
- Accepts existing interchangeable devices, mouse, or pen wands and the customized QC3800V for screening

Durable

Built to last with no internal moving parts and a 2 year warranty make the QC890 one of the best verifiers on the market.

Standard Features

Compliance

Meets ISO/IEC 15426-1 Bar code verifier conformance specifications Part 1: Linear Symbols.

Bar Code Symbol Support

Tests major symbologies and industry applications against ISO/IEC 15416 Bar code print quality test specification - Linear symbols and Traditional Pass/Fail parameters.

Intuitive User Feedback

Options for application-specific “good read” LED and beeper settings coupled with Quick Check® ImageData software setup and operation.

Quick Check 890 Specifications



Dimensions

Height: 6.0 in. (15.3cm)
Width: 6.9 in. (17.6cm)
Depth: 5.5 in. (13.9cm)

Mechanical

Standard Hardware

Configuration: Optical Input Device (OID), interface, power supply
Optical Input Connector: 9-pin plastic squeeze-to-release male
I/O Connector: 10-pin modular (allows for I/O communications with computer)

Power:

Interface	Maximum Current Draw from Host	Maximum Current Draw Low Charge Mode
USB@5V	500mA	500mA
External Power @5V	1000mA	500mA

Beeper:

For audible user feedback of verification results

LEDs:

Red and green LEDs indicate charge state of the internal battery, verification results, and host communication state

Interfaces

RS-232, Bluetooth® 1.2, (Class 2) (10 meter range), USB 1.1 (2.0 compatible)

System Requirements

Windows

Microsoft Windows 98, 2000, Windows NT or XP operating system
Pentium 100Mhz (recommend 500Mhz and up)
64 MB RAM (recommended 128 MB and above)
Application: 5 MB available hard disk space
.NET framework: 110 MB of hard disk space required, 40 MB additional hard disk space required for installation (150 MB total)
Any available COM or USB port or Bluetooth (supports SPP profiles)
Microsoft compatible mouse

Windows Mobile 2003:

Windows CE .NET 4.2 or Pocket PC 2003/2003 SE
ARM4 processor
64 MB RAM (2MB RAM for the application)
Any available COM port, Bluetooth (supports SPP profiles)

Optical

Sensor:

Linear CCD imager, bi-directional scanning

Test Aperture:

5, 6, and 10 mil internal (automatic and manual configuration options)
3, 5, 6, 10, and 20 mil external

Wavelength:

660 nm (internal optics)

Read/Scan Width:

5.3 in. (13.5cm) including quiet zones/light margins

Environmental

Operating Temperature:

50° to 104°F (10° to 40°C)

Storage Temperature:

32° to 104°F (0° to 40°C)

Relative Humidity:

25% to 80% @ 40°C non-condensing

Warranty:

2 years

Symbologies:

EAN/UPC with addenda, Code 39 (1-49 characters), Interleaved 2 of 5 (2-78 characters), Codabar, Code 128 (1-70 characters), MSI (1-50 characters), Code 16K (individual rows), Code 49 (individual rows), Code 93, Code 11, Regular 2 of 5 (discrete/industrial 2 of 5), IATA 2 of 5 (straight 2 of 5), Reduce Space Symbology (RSS), PDF417, and Telepen...others to be added.

Applications:

ITF-14, and UCC/EAN 128

Multiple Language Support:

English, Chinese, Japanese

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Hand Held Products.

IBM is a registered trademark of International Business Machines, Inc.

Microsoft® Windows® 98, 2000, NT, XP, and Windows Pocket PC are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa

Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France

Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com
Shanghai
Tel: +86 21 6361 3818
appresales@handheld.com

Offices Serving Latin America

Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com
São Paulo
Tel: +55 11 2178 0500
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2178 0500
lapresales@handheld.com
Mexico
Tel: +52 55 5203 2100
lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") ©1999-2006. All rights reserved. Printed in the U.S.A.

Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.



BARCODING, WIRELESS AND DATA COLLECTION

Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.

TPI will facilitate your entire wireless and data collection project:

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.

Product specification sheet provided by TPI

www.tpi1.com
888-488-4244

