

Product Profile

- Supports industry standard communications
- 2.4 GHz or 802.11b 11 Mbps radio
- Fast and easy integration options for terminal emulation or client/server
- Flexible connectivity choices
- Large, high contrast display
- Rugged casing



2 4 2 5 D S H A N D H E L D C O M P U T E R

The 2425 DS is the Intrinsically Safe, more ruggedized wireless model of the 2400 family hand-held line of data collection terminals. It is a cost-effective and reliable solution for collecting data in manufacturing, distribution and warehouse environments. The Intrinsically Safe model provides protection in hazardous areas containing gas, vapors and dust.

For fast and easy implementation, the 2425 DS integrates with common host environments using standard protocols. Configure the 2425 DS with TCP/IP for a direct connection to your Ethernet or

Token Ring LAN or connect to Ethernet and IBM networks through the DCS 300 Server, which also provides guaranteed host connection and network management services.

With a contoured shape and centered scan button, the 2425 DS is comfortable to use in either hand. The large display provides enough space for menus, help screens or even graphics. It is tilted to improve readability while scanning, and the alphanumeric keyboard provides tactile feedback with the frequently used numeric keys oversized for easier input.

Physical Characteristics**Length:** 26.9 cm (10.6")**Height:** 7.1 cm (2.8") at scanner, 5.7 cm (2.3") at grip**Width:** 8.2 cm (3.2") at scanner, 6.4 cm (2.5") at grip**Weight:** 766 g (27 oz.) including battery**Environment****Operating:** -20° to 50°C (-4° to 122°F)**Storage:** -20° to 60°C (-4° to 140°F)**Humidity:** Non-condensing (0 to 95% RH)**Shock and Vibration Protection:**

Warranted for 5-foot drop to concrete

Meets MIL-STD 28800E

Power**Operating:** Lithium Ion battery pack**Memory Backup:** Rechargeable NiCad**Memory****RAM Memory:** 1MB**Non-volatile Flash Memory:** 4MB**Interfaces**

- Optical Serial Interface
- RS232-C up to 38.4 baud
- XMODEM, YMODEM for data transfer

Display

- CGA compatible backlit LCD displaying 16 lines of 20 characters per line (160 x 128 dot matrix) plus graphic status icons

Keyboard

- Elastomeric 56-key with full alphanumeric set, function keys and oversized numeric
- Options for U.S., Multilingual European, IBM 5250, IBM 3270 and VT/ANSI layouts

Software**Programmable:** Microsoft® C/C++, EzBuilder**Terminal Emulation:** IBM 3270 and 5250 SNA and TELNET; ANSI/VT 100, 220, 320 TELNET; Screen mapping**Web-based:** dcBrowser™ for HTML applications**Connectivity**

- Direct TCP/IP Support
- DHCP Client
- Sockets interface or terminal emulation

Bar Code Symbolologies

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN Code 128, Code 11, Code 93, Plessey, MSI, Code

Bar Code Scanning Options

Integrated visible laser diode scanner

USA/Canada Class II, International Class 2

Depth of Field*—Standard Range (670nm)

5 mil	9.4-15.7cm	3.7-6.2"
10 mil	7.4-35.3cm	2.9-13.9"
20 mil	10.2-63.5cm	4-25"
30 mil	10.2-86.4cm	4-34"
40 mil	12.7-99cm	5-39"
55 mil	19.1-126cm	7.5-49"
55 mil retroreflective	105-151cm	41-59"
100 mil retroreflective	113-227cm	44-89"

Depth of Field*—Long Range (650nm)

5 mil	29.5-49.8cm	11.6-19.6"
10 mil	21.8-85.3cm	8.6-33.6"
20 mil	21.8-98cm	8.6-38.6"
30 mil	24.4-192cm	9.6-75.6"
40 mil	24.4-204.7cm	9.6-80.6"
70 mil retroreflective	192-410.5cm	76.6-161.6"
100 mil retroreflective	212.3-532.4cm	83.6-209.6"

*Measured for Code 39

- High Density and High Performance

Integrated RF Module**Frequency:** 2.4 GHz frequency band, actual frequencies in use vary by country**WLI Forum OpenAir****Type:** Frequency Hopping Spread Spectrum**Data Rate:** 1.6 Mbps, .8 Mbps fallback**Range*:** From 1500+ ft (450+ m) to 500 ft (150 m) depending on environment**IEEE 802.11b Wi-Fi Certified****Type:** Direct Sequence Spread Spectrum**Data Rate:** 11/5.5/2/1 Mbps with Auto

fallback for increased range

Range* at 1 Mbps: From 1750 ft (533 m) to 165 ft (50 m) depending on environment**Range* at 11 Mbps:** From 525 ft (160 m) to 80

ft (24 m) depending on environment

Security: Wired Equivalent Privacy (WEP) - 64 or 128 bit encryption

*Unlimited range with roaming

Host Support via DCS 300 Server**Host Environment:** IBM AS 400, S/390, Digital, HP, UNIX, Windows NT**Connectivity:** Ethernet, Token Ring, 100BASET, Twinax, Coax, SDLC**Communications:** TCP/IP, SNA**Accessories (not certified for use in hazardous areas)**

Handstrap, holster, belt clip, pistol grip handle, vehicle mount holder, battery charger, battery pack, serial adapter and communications dock, User manuals, Programmer's Software Kit (PSK)

Intrinsically Safe Model 2425 DS

Please contact your Intermec representative for configurations available

Regulatory Approvals

UL Listed, UL 913 and C22.2 No. 157 Division 1: Class I-Groups C & D

UL Listed UL1604 & C22.2 #213 Division 2, Class I Groups A, B, C & D

UL Listed UL 1604 only Division 2, Class II Groups F & G


SIRA Certified to CENELEC EN 50020 and ATEX Directive.

Rated EEx ia IIB T4.

Australia / New Zealand: Simtars Certified - IEC 60079-0 / -11 Rated Ex ia I / IIB T4

All other 2425 accessories usable but not certified.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.



North America
Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada
 7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

**Europe/
 Middle East & Africa
 Headquarters**
 Reading International Business Park
 Basingstoke Road
 Reading RG2 6DD
 United Kingdom
 tel: 44.118.923.0800
 fax: 44.118.923.0801

**Asia
 Asia Regional Office**
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office
 29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86.10.5165.5922
 Fax: 86.10.6567.6778

Australia
 Level 4, 1-3 Atchison Street
 St. Leonards, NSW 2065
 Australia
 tel: 61.2.9330.4400
 fax: 61.2.9437.0204

**South America & Mexico
 Intermec South America Ltda.**
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico
 Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.241.4800
 fax: 525.55.211.8121

Internet
 www.intermec.com

Sales
 800.934.3163
 (toll free in N.A.)
 tel: 425.348.2726

OEM Sales
 tel: 425.348.2762

**Customer Service and
 Support**
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
 611762-01A 06/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



BARCODING, WIRELESS AND DATA COLLECTION

Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.

TPI will facilitate your entire wireless and data collection project:

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.

Product specification sheet provided by TPI

www.tpi1.com
888-488-4244

