



Intermec

Product Profile

- Compact, industrial design
- Robust data collection
- Industry standard development and connectivity tools
- Flexible application environments



2480 SERIES STATIONARY COMPUTER

The 2480 Series Stationary Terminal delivers timely, accurate data for mission critical manufacturing systems. With a compact metal case, environmental sealing and power protection, the reliable 248X handles the most punishing industrial plants. It's ideal for work in process tracking, labor collection, and time and attendance applications.

The 2480 Series Stationary Terminal includes two ports for bar code input devices and a serial port to connect a printer or scale. An optional integrated badge scanner, digital input/output and two additional serial ports accommodate the most demanding data collection requirements.

Choose Ethernet or serial connections to host computers. The 2480 Series supports client/server and terminal emulation host environments. It's also compatible with Intermec CrossBar® networks.

The 2480 Series Stationary Terminal is programmable using industry standard, Microsoft® C/C++. Using standard tools you can dramatically reduce development time and cost for creating shop floor solutions.

A large, stylized outline of the Intermec logo at the bottom of the page.

Physical Characteristics

Height: 24.4 cm (9.6")
Length: 27.2 cm (10.7"); 28.7 cm (11.3") with badge scanner
Depth: 9.9 cm (3.9")
Weight: 4.3 kg (9.5 lbs)

Environment

Operating temperature: -20° to 50°C (-4° to 122°F)
Storage temperature: -20° to 60°C (-4° to 140°F)
Humidity: Non-condensing (0 to 95% RH)
Sealing: Die cast aluminum case. NEMA5/IP53 sealing for dust, moisture and splashing.

Power

Operating: 95 - 250 volts AC, 50/60 Hz
Power protection: Handles 1 second dropouts
Memory Backup: Rechargeable NiCad battery pack

Memory

RAM: 1MB Total
Non-volatile memory: 2MB; option for 2MB additional, 4MB total
Extended Memory: 2MB Flash; 2MB or 4MB SRAM

Displays

CGA compatible LCD with backlight
2481/86: 12 lines by 40 characters per line
 Display up to 24 lines

Keyboards

Alphanumeric: 59 key elastomeric; PC style QWERTY layout; 5 shiftable function keys
Oversized function/numeric: 35 key elastomeric; 10 separate function keys
Time and Attendance: 35 key membrane, 10 separate function keys
Terminal Emulation: templates for IBM 5250, IBM 3270 and ANSI/VT

Input Ports

2 bar code input ports
Digital input/output: 4 optically isolated sense inputs; 4 two form C output relays, dry contacts
 External speaker connection

Bar Code Symbolologies

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN, Code 128, Code 11, Code 93 and 93i, Plessey, MSI, Code 16K, PDF-417 supported using tethered scanner

Wired Data Communication

2481:
Ethernet: 10BaseT
Serial Ports: RS-232, RS-232/422/485

Integrated RF Module

2486:
Frequency Band: 2.4 GHz frequency band, actual frequencies in use vary by country
WLI Forum OpenAir
Type: Frequency Hopping Spread Spectrum
Data Rate: 1.6 Mbps, .8 Mbps fallback
Range*: From 1500+ ft (450+ m) to 500 ft (150 m) depending on environment

IEEE 802.11b Wi-Fi Certified

Type: Direct Sequence Spread Spectrum
Data Rate: 11/5.5/2/1 Mbps with Auto fallback for increased range
Range* at 1 Mbps: From 1750 ft (533 m) to 165 ft (50 m) depending on environment
Range* at 11 Mbps: From 525 ft (160 m) to 80 ft (24 m) depending on environment
Security: Wired Equivalent Privacy (WEP) - 64 or 128 bit encryption
 * Unlimited range with roaming

Host Support Direct Connect

Host Environment: IBM AS/400, S/390, Digital, HP, UNIX with Telnet Services
Connectivity: Ethernet, serial
Communication: TCP/IP, XMODEM/ YMODEM
Terminal Emulation: TN 5250, TN 3270, VT/ANSI

Host Support via DCS 300 Server

Host Environment: IBM AS/400, S/390, Digital, HP, UNIX
Connectivity: 10/100 Mbps Ethernet, Token Ring, Twinax, Coax, SDLC
Communications: TCP/IP, SNA, TCP/IP socket pass through
Terminal Emulation: IBM SNA 5250, 3270, ANSI/VT 100, 220, 320, and Screen Mapping
Web-based: dcBrowser™ for HTML applications

Language Support

English, German, French, Italian, Spanish, Portuguese, Chinese, Japanese, Korean and Thai. Localized fonts, keypads and Getting Started Guide. Supports additional single and double byte fonts.

Badge Scanner

- Visible light badge scanner
- Infrared light badge scanner

Accessories

Wall or desk mount brackets, Programmer's Software Kit (PSK), Adapter for third serial port (9 pin RS-232)

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TÜV GS Licensed, EN 60950, FCC Part 15, Canada, RSS210 and ICES 003 Class B, EN 55022/CISPR 22, Class B, ETS 300 826, ETS 300 328, Compliant with European Directives CE Marked

North America

Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada
 7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

Europe/

**Middle East & Africa
 Headquarters**
 Reading International Business Park
 Basingstoke Road
 Reading RG2 6DD
 United Kingdom
 tel: 44.118.923.0800
 fax: 44.118.923.0801

**Asia
 Asia Regional Office**
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office
 29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86.10.5165.5922
 Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
 St. Leonards, NSW 2065
 Australia
 tel: 61.2.9330.4400
 fax: 61.2.9437.0204

**South America & Mexico
 Intermec South America Ltda.**
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico
 Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.241.4800
 fax: 525.55.211.8121

Internet

www.intermec.com

Sales
 800.934.3163
 (toll free in N.A.)
 tel: 425.348.2726

OEM Sales
 tel: 425.348.2762

Customer Service and Support
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608322-01F 04/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





BARCODING, WIRELESS AND DATA COLLECTION

Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.

TPI will facilitate your entire wireless and data collection project:

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.

Product specification sheet provided by TPI

www.tpi1.com
888-488-4244

