

Product Profile



- Dense reader mode enables superior adjacent dock door reading
- Conveyor reading up to 1600 fpm
- Directly monitors and controls presence detectors and signal lights
- Multi-protocol reading and writing of UHF RFID tags
- Factory configurable to operate in 865MHz, 869MHz or 915MHz RFID bands
- On-board device management
- Built in power supply

IF30 FIXED READER

The IF30 is a cost-effective, high performance fixed reader that reliably reads and writes UHF RFID tags in “RF noisy” environments. The IF30’s receive sensitivity enables large populations of tags to be interrogated at high speeds, which is critical to many use cases involving dock doors, portals and conveyors. In addition to reading tags at distances over 15 feet (4.6 meters), the IF30 can filter tag data to prevent sending redundant information to the host system.

With best in class Dense Reader Mode performance, the IF30 fixed reader allows users to grow their RFID operations to include multiple dock doors in close proximity, thus enabling accurate, automated receiving and shipment verification. This drives more effective put away processes.

Increased receive sensitivity allows the IF30 to interrogate weaker/unreadable tags that often lead to expensive exception handling processes and slower supply chain throughput.

Unlike all competitors, the IF30 has a built-in power supply and 4 mono-static RF ports which reduce the costs and complexity at installation with fewer component pieces to complete the overall solution.

Continuing to focus on keeping the costs of ancillary equipment and installation low, the IF30 fixed reader includes powered general purpose input/output (GPIO) circuitry, which allows direct monitoring and/or controlling of peripherals such as presence detectors and signal lights without requiring extra devices and power supplies to facilitate the connection.

Intermec SmartSystem® Foundation, a device management system included on the IF30, lets you view and configure all of the settings contained in the device from one convenient location allowing for a quicker set-up.

SmartSystems-enabled devices appear on an administrator’s console, providing real-time visibility to device status and information, and centralized access to remote devices like the IF30 reader.

The intuitive console allows administrators to change device settings, send firmware upgrades, update software applications, and execute other changes directly from the console to save time and significantly cut costs.

The IF30 reader is also supported by Intermec’s RFIDeploy Services which provide process analysis, site analysis and installation. By deploying the full suite of services, your

system performance will be guaranteed for 18 months, or you may simply select the service that will facilitate the completion of your RFID roll out.

In support of a global supply chain, the IF30 is FCC and ETSI certified, and is factory configured to operate in RFID frequency bands 865MHz, 869MHz and 915MHz.

Physical Description

The IF30 is an UHF fixed reader that can be factory configured to operate in RFID frequency bands: 865MHz, 869MHz and 915MHz. In addition to performing both read and write functions, the IF30 has built in general purpose input output (GPIO), 4 mono-static RF ports and a built-in power supply.

Physical Characteristics

Length: 32.35 cm (12.74 in)

Width: 22.60 cm (8.90 in)

Height: 8.25 cm (3.25 in)

Weight: 6.75lbs (3.06 Kg)

Environment

Operating Temperature: -20°C to 55°C (-13° F to 131° F)

Storage Temperature: -30°C to 75°C (-22° F to 167° F)

Humidity: 10% to 90% (Non-condensing)

Enclosure: IP53

Standard Features

Communications Interface options:

Ethernet 10/100BaseT and RS232 for configuration

Configuration: Internal web Graphical User Interface (GUI)

General Purpose Input/Output (GPIO): Four input (0-40VDC) and four output (0-48VDC .25 amp) circuits, 500ma 12VDC power

Antenna Connections

Four – Connectors: FCC-Reverse SMA. ETSI Standard SMA, 30 dBm to 10dBm RF power output software controlled

Power

110-240 VAC auto ranging
Power Supply is internal and included
Duty Cycle: 100%

RFID Frequency Ranges

865, 869 and 915 MHz

Tag Air Interfaces

Fairchild G1
ISO 18000-6b
ISO 18000-6c
Philips Version 1.19
EPCglobal UHF Gen 2

Application Protocols

ANSI INCITS 256:2001
Intermec Basic Reader Interface

Connectivity

Ethernet IPv4 & IPv6
RS232 for configuration

Software

Syslog Client
HTTP/HTTPS Web Server
TFTP Client
DHCP Client
DNS Client
SNTP Client

Security

OpenSSL
Radius configuration login

Device Management

SNMP
Intermec SmartSystems™ client
Wavelink Avalanche™ Client

Accessories

Antennas, antenna cables, mounting bracket

Standards

AIAG B-11
ANSI MH10.8.4
ISO/IEC CD18000 Part 4
ISO/IEC WD18000 Part 6
IF30 uses the IM5 module, which is EPC Certified Compliant and EPC Certified Interoperable.

Restrictions on Use

Some approvals and features may vary by country and may change without notice. Please check with your local Intermec sales office for further information.

Disclaimer

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.



North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/ Middle East & Africa Headquarters

Reading International Business Park
Basingstoke Road
Reading RG2 6DD
United Kingdom
tel: 44.118.923.0800
fax: 44.118.923.0801

Asia

Asia Regional Office
#05-02A/03 New Tech Park
151 Lorong Chuan
Singapore 556741
tel: 65.6303.2100
fax: 65.6303.2199

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
118 Jian Guo Road
Chaoyang District, Beijing 100022
Tel: 86.10.5165.5922
Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
St. Leonards, NSW 2065
Australia
tel: 61.2.9330.4400
fax: 61.2.9437.0204

**South America & Mexico
Intermec South America Ltda.**
Rua Samuel Morse 120 9 andar
Brooklin CEP04576-060
São Paulo, SP
Brazil
tel: 55.11.5502.6770

Intermec Technologies de Mexico
Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.241.4800
fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.934.3163
(toll free in N.A.)
tel: 425.348.2726

OEM Sales

tel: 425.348.2762

Customer Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2007 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611799-01A 01/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



BARCODING, WIRELESS AND DATA COLLECTION

Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.

TPI will facilitate your entire wireless and data collection project:

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.

Product specification sheet provided by TPI

www.tpi1.com
888-488-4244

