

## Product Profile



- Superior throughput eliminates wait time at the printer
- Heavy-duty metal construction withstands harsh / rugged environments
- Integrated EasyLAN™ Ethernet, USB and serial interface standard
- Compact Flash memory for quick and easy firmware, font and memory upgrades
- Supports stand-alone printer applications
- Easily adapts to changing host environments and applications
- Emulates and replaces competitive and older Intermec printers
- Utilize up to five interface ports simultaneously, including internal EasyLAN Wireless
- Magnetic QuickMount™ printhead for easy printhead installation
- User selectable printer language
- Double-clutching ribbon mechanism supports ribbons wound in either direction

### EasyCoder® PM4i PRINTER

Are you looking for more efficient processes, reduced costs, and increased production?

The EasyCoder PM4i is an industrial printer designed to excel in demanding applications and environments. Utilizing the latest technology, the PM4i features a strong and proven mechanical platform, and powerful newly developed electronics.

The EasyCoder PM4i printer acts as a "smart client" executing user-defined programs. This means your PM4i printer eliminates the personal computer, operates additional hardware (e.g. scanners, other printers, conveyors), accesses information from network host, and retains the ability to change as needed with the application for additional functionality. When using the EasyLAN™ Wireless option for the PM4i, any attached peripheral devices also become part of the wireless infrastructure.

Printer command languages do not restrict the EasyCoder PM4i bar code label printer. The printer can be changed to understand and replace competitive and older Intermec printers without requiring any changes to the host programming or label formats that are currently being used.

The EasyCoder PM4i includes integrated wired or wireless EasyLAN networking. The EasyLAN Wireless interface uses an integrated standard 802.11b radio. This radio provides 128-bit WEP encryption of the information relayed through the network. Intermec's wired and wireless technology ensures secure printing and network infrastructure for all environments.

This is an extremely versatile bar code label printer. There are up to five interface ports that can be used simultaneously. The EasyCoder PM4i includes serial, parallel, USB, internal EasyLAN Ethernet, and EasyLAN Wireless. The magnetic QuickMount printhead eliminates hassles and the need to call a service technician. The printhead is replaced quickly and easily with the magnet and u-brackets ensuring proper alignment. The double-clutching ribbon mechanism means that you are no longer restricted to ribbon types based on how they are wound. The handy, inexpensive and PC-compatible Compact Flash memory technology provides quick and easy upgrades of firmware, fonts and memory.

The EasyCoder PM4i printer is exceptionally fast in throughput and printing, reliable, and delivers very high print quality.

**Application**

Direct Thermal and Thermal Transfer label, ticket and tag printer.

**Physical Characteristics**

**LxHxW:** 54.3 x 26.1 x 29.8 cm  
(21.38 x 10.28 x 11.73 in)  
**Weight:** 13.5 kg (29.76 lbs.)

**Print Specifications**

**Max. Width:** 104 mm (4.09 in) at 203 dpi; 105.7 mm (4.16 in) at 300 dpi.  
**Max. Length w/ std memory:** 2520 mm (99.2 in) at 203 dpi; 1092 mm (43.0 in) at 300 dpi.  
**Max length w/ 16MB SDRAM:** 4095 mm (161.2 in) at 203 dpi; 2730 mm (107.5 in) at 300 dpi.

**Print Speed**

Up to 76 labels per minute. 101x152mm (4x6 in) GM1724 label. To learn more about print speed, please visit [www.intermec.com/printspeed](http://www.intermec.com/printspeed).

**Print Direction**

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

**Print Resolution**

8 dots/mm (203 dpi); 11.8 dots/mm (300 dpi)  
\*300 dpi available for Fingerprint / DP protocols only

**Label/Ticket/Tag**

**Max. Width:** 114.3 mm (4.5 in)  
**Min. Width:** 25.4 mm (1 in)  
**Thickness:** 2.5 to 7 mil  
**Style:** Roll-fed, die-cut, continuous or fanfold labels, tags or tickets  
**Label Roll max diameter:** 213 mm (8.38 in)  
**Label Roll Core:** 38-76 mm (1.5-3 in)  
**Media Type:** Thermally sensitive media

**Ribbon Roll**

**Ribbon roll max diameter:** 83 mm (3.27 in) or approx. 450 m (1475 ft) of ribbon  
**Ribbon Roll Core:** 25 mm (1 in)  
**Ribbon Type:** Wax, wax/resin, resin

**Interface****Standard:**

- RS-232, up to 115.2 kB/s
- USB 1.1
- EasyLAN Internal Ethernet 100/10BaseT
- I2C-bus for cutter
- Wand interface for EasySet™ System

**Optional**

- EasyLAN Wireless, internal 802.11b/g Wireless Ethernet

**Optional interface card adapters (any 2 can be fitted simultaneously):**

- Parallel IEEE 1284

- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

**EasyLAN Ethernet Network Interface:**

Internal High Speed Ethernet  
**Ethernet:** RJ-45 connector for 10baseT Ethernet or 100baseTX Fast Ethernet  
**Supported protocols:** TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP.  
SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

**EasyLAN Wireless**

- Fully integrated IEEE 802.11b
- WEP 128 bit
- Supports IEEE 802.1x (LEAP, PEAP, TTLS, WPA) security
- Multiple industrial antenna options for maximized coverage

**Software****Available printer command languages:**

- IPL
  - Fingerprint/Direct Protocol
- Applications/Drivers (comes on Printer Companion CD) including:**

- InterDriver™ Windows printer driver
- Intermec LabelShop® START label design and print package
- Intermec Printer Network Manager for administration of network connected printers
- PrintSet for printer configuration

**Optional software for application development:**

- Fingerprint ApplicationBuilder
- Intermec Printer Application Server
- ERPLabel for SAP R/3.

**Bar Code Symbolologies**

**1-dimensional:** Codabar, Code 11, Code 39, Code 93, MSA (modified Plessey), Code 128, Code 128 Subset A-C, DUN-14/16, UPC/EAN Codes (EAN 8, EAN 13, UPC Version A, UPC Version E), EAN-128, EAN-128 Subset A-C\*, Industrial 2 of 5, Interleaved 2 of 5, Interleaved 2 of 5 A, Matrix 2 of 5\*, Planet, Postnet, Straight 2 of 5\*, UCC-128 Serial Shipping Container Code, RSS, HIBC Code 39 (IPL only), HIBC Code 128 (IPL only), JIS-ITF (IPL only)  
**2-dimensional:** Code 16K, Code 49, Data Matrix, MaxiCode, PDF417, QR Code, MicroPDF417, EAN.UCC Composite

**Standards Supported**

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS shipping label; Global Transport label

**Characters Sets**

**Fingerprint/DP:** 15 TrueType™ fonts including 12 UNICODE (1 WGL4), 1 symbol, 1 OCR-A, 1 OCR-B. All fonts are scalable. Font cache for maximum performance. ATF font support.  
**IPL firmware:** 13 TrueType fonts and 20 bitmap fonts.

Non-Latin fonts are available as options.

**Graphics**

Supports PCX file format.

**Memory**

**Standard:** 4MB Flash  
8MB SDRAM  
1 Compact Flash slot  
**Optional:** Additional FLASH memory up to 16MB (8+8)  
1GB Compact Flash memory

**Protocol**

**Fingerprint/Direct Protocol:** XON/XOFF, ENQ/ACK, DTR, RTS/CTS  
**IPL:** XON/XOFF, Intermec Std. Protocol

**Display**

Back-lit LCD for 2x16 characters and 3 LED indicator lamps

**Keypad Control Panel**

- Full keypad control panel (Fingerprint/DP)
- Reduced keypad control panel (IPL)

**Power Supply**

115/230VAC auto-switch w/PFC  
**Voltage range:** 90-264VAC.  
**Frequency Range:** 45-65 MHz

**Operating Environment**

**Temperature:** +5°- 40°C (+40°- 104°F)  
**Humidity:** 20-80% RH non-condensing  
**Noise:** 50 dB (printing), no noise standby

**Regulatory Approvals**

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

**Options**

Integral Self-Strip unit with Liner Takeup, Label Taken Sensor (LTS), Compact Flash (CF) memory, Flash and SDRAM SIMM memory, Various International Double Byte Fonts, EasySet bar code Wand\*, Keyboard Converter\*, Parallel Interface board, Additional Serial Interface board, Industrial Interface board\*, Real Time Clock\*, Media supply hub, Cutter, Label low sensor

\*Not applicable when using IPL firmware

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/**

**Middle East & Africa  
Headquarters**  
Sovereign House  
Vastern Road  
Reading RG1 8BT  
United Kingdom  
tel: 44.118.987.9400  
fax: 44.118.987.9401

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

**Beijing Representative Office**

29 FL, Unit A1, China Merchant Tower  
118 Jian Guo Road  
Chaoyang District, Beijing 100022  
Tel: 86 10.5165.5922  
Fax: 86 10.6567.6778

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest, NSW 2065  
Australia  
tel: 61.2.9492.4400  
fax: 61.2.9954.6300

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Samuel Morse 120 9 andar  
Brooklin CEP04576-060  
São Paulo, SP  
Brazil  
tel: 55.11.5502.6770

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.211.1919  
fax: 525.55.211.8121

**Internet**

[www.intermec.com](http://www.intermec.com)

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2004 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611307-01B 12/04

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

**Intermec**  
e x p e c t **MORE**



## BARCODING, WIRELESS AND DATA COLLECTION

*Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.*

*TPI will facilitate your entire wireless and data collection project:*

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

*TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.*

Product specification sheet provided by TPI

**www.tpi1.com**  
**888-488-4244**

