

Intermec

Product Profile

- Exceptional reading performances: very fast, for contact and non contact applications (up to 49.2 cm/19.4")
- Read long, damaged, poorly printed barcodes and extremely small bar widths (0.05mm, (2mils))
- Long life time and high reliability
- Light weight, bright and sharp scan line for easy use
- Harmless illumination for a safer working environment
- Cost efficient for contact and non-contact scanning



SCANPLUS® 1800 VISTA SCANNER

Combining the benefits of CCD & Laser technologies, the ScanPlus 1800 Vista is the ultimate user's choice. New Intermec developments in decoding and scanning resulted in:

Unique reading performances

The S1800VT succeeds in reading barcodes at 49.2 cm (19.4") distance with a scan rate of up to 225 scan/sec. Snappy response and easy aiming makes it very comfortable to use.

Also, it can read any type of codes, whether they are poorly printed, damaged, 18cm (7") long, or if they incorporate code 39 with a barcode width of 0.05mm/0.2mil (unique in the market place). It is operational in any lighting conditions, from total darkness to full exposition to sun light (100,000 lux).

Comfortable to use

The S1800VT inherits the ergonomics and light shape of the ScanPlus 1800 family. Aiming is very easy thanks to the sharp and bright scanning line (specific LED system).

Reliability

The S1800VT incorporates no moving parts. For this reason, it has a longer life than any laser scanner. It withstands

multiple drops to concrete from 1m (3.2') and can be used in a wide temperature range.

Flexibility

ScanPlus 1800 Vista is compatible for contact and non contact applications. Also, it is compatible with more than 400 host interfaces, including OLEpos and USB. All standard 1D symbologies are available, as well as PDF 417. Future upgrades or special applications are easily implemented using flash memory.

Safe to use

Laser scanners can be harmful if the user looks accidentally into the beam. For ScanPlus 1800 Vista, the illumination is produced by LEDs that are absolutely safe for the user.

Cost efficient solution

Unique reading performances, snappy, extended reading distance, reliability, flexibility, safety, ergonomics, easy set up... All these benefits gathered at an extremely competitive price. In fact, the S1800VT is the answer for most of the applications and for all budgets.

As any member of the ScanPlus 1800 range, the S1800 VT is compatible with EasySet™ set up software for the fastest on line or off line configuration.

General Description

A high performance and compact CCD handheld scanner for non-contact applications. Designed for Retail, Health Care, Office & light Industrial environments.

Scanning Performances

Scanrate: S1800 VT: 225scan/s
Min. x dimension: down to 0.05mm (2 mil) (Intermec decoding technology)
Depth of field : from 0cm to 49.2cm (19.4")

Bar width		Max. distance*		Max. distance on code 39**	
mm	mil	cm	inch	cm	inch
0.1	4	16.2	6.4	23.0	9.0
0.2	8	23.0	9.0	26.4	10.4
0.3	12	26.2	10.3	36.0	14.17
0.5	20	34.5	13.6	49.2	19.4
1	40	49.2	19.4	49.2	19.4

* From scan-engine
 ** Advanced Intermec decoding technology used

Bar code width: up to 18cm (7") on 0.3mm/12mil resolution code
Print Contrast: down to 25%
Scan Angle: 48°
Skew: +- 35°
Pitch: +- 35°

Bar Codes Supported

UPC (E&A); EAN; Code 39; Interleaved Matrix, Industrial & Standard 2 of 5; Code 128, UCC EAN 128, Codabar, Code 93, ISBN, MSI, Plessey, Telepen

Host Interfaces

USB, OLEpos, Wand & Laser emulation, single/dual RS232, IBM 46xx, OCIA, HP700/xx, PC AT/PS2 wedge to over 400 terminals & PC. Extensive interface information on application.

Operator Feedback

Green good read LED. Adjustable beeper.

Design Features

Processor: Custom chip (ASIC inc. DSP processor) for fast signal processing and decoding. Flash memory.
Optics: 645 nm visible red Top LED. Bright & sharp scanning line.

Environmental Characteristics

Operating Temperature: 0 – 50°C (32 – 122°F)
Storage Temperature: -25 – 70°C (-11 – 160°F)
Relative humidity: 5% to 95% (non condensing)
Shock: withstands multiple 1m (3.2') drops to concrete
Ambient illumination: works in any lighting condition, from 0 to 100,000 lux.

Electrical Characteristics

S1800 VT: 140mA (average) and 40mA (stand by)

Physical Characteristics

Length: 180mm (7")
Width at handle: 33mm (1.3")
Width at head: 64mm (2.5")
Standard cable: 1.8m (70")
Weight without cable: 140g
Case: High-impact ABS self-extinguishing plastic. Rubber end cap and boot.

Special Features

Firmware updates via flash memory, programmable data format (code identification, preambles & postambles, intercharacters & intermessage delays, variable time-out, and many others).

Configuration

Fast & easy set up with EasySet™ Windows software

Accessories

Desk/vertical holder
 Raised hands-free stand (option)

Regulatory Approvals

UL Listed, TÜV-GS, NOM certified.
 Complies with FCC rules part 15, CE mark, Australian C-TIC, Canadian ICES 003.

North America
 Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

Systems & Solutions
 550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Europe/ Middle East & Africa
 Headquarters
 Sovereign House
 Vastern Road
 Reading, Berkshire RG1 8BT
 United Kingdom
 tel: +44.118.987.9400
 fax: +44.118.987.9401

Gothenburg
 Idrottsvägen 10
 P.O. Box 123
 SE-431 22 Mölndal
 Sweden
 tel: +46.31.869500
 fax: +46.31.869595

Asia/ Latin America
 Hong Kong
 26-12 Shell Tower
 Times Square
 1 Matheson Street
 Causeway Bay
 Hong Kong
 tel: 852.2574.9777
 fax: 852.2574.9725

Singapore
 25-16 International Plaza
 10 Anson Road, 079903
 tel: 65.324.8391
 fax: 65.324.8393

Australia
 Level 7, 200 Pacific Highway
 Crows Nest NSW 2065
 Australia
 tel: 61.2.9901.2065
 fax: 61.2.9954.6300

South America and Mexico
 17921 B Skypark Circle
 Irvine, California 92614
 tel: 949.442.9393
 fax: 949.757.1687

Worldwide Fax Document Retrieval Service
 800.755.5505
 (North America Only)
 tel: 650.556.8447

Internet
 www.intermec.com

Sales
 800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 609058-01B 10/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



BARCODING, WIRELESS AND DATA COLLECTION

Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.

TPI will facilitate your entire wireless and data collection project:

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.

Product specification sheet provided by TPI

www.tpi1.com
888-488-4244

