



Intermec

## Product Profile



### S F 5 1 C O R D L E S S S C A N N E R

- **Unique design enables users to increase productivity with truly "hands-free" scanning**
- **Bluetooth™ radio communication eliminates cables and facilitates complete mobility**
- **Interfaces with Intermec terminals and personal computers**
- **Intermec EV10 linear scan engine delivers unparalleled flexibility reading high density, PDF and standard range bar codes**
- **Industrial durability stands up to harsh environments and multiple drops**
- **Small size is easily articulated for quick scanning**

Intermec's SF51 scanner incorporates a unique, light weight form factor with a magnetic attach/release mechanism to maximize productivity. The unique patent pending design takes "hands free scanning" to a new level. Instead of mounting the scanner onto the user's hands or fingers and thereby restricting use, the SF51 is designed to be worn on the waist, wrist, or chest. The attach/release mechanism can be used without looking at it. This allows the user to quickly and easily access and release the scanner when it's needed, and when done scanning, reattach the SF51 for un-inhibited use of their hands.

An extremely durable scanner with a wireless personal area network (PAN) radio based on Bluetooth™ communication protocol, the SF51 can cordlessly connect to Intermec terminals without a base station, delivering an affordable, high performance solution for scan intensive applications.

The SF51 utilizes the Intermec EV10, an innovative linear scan engine with new APS CMOS technology. It delivers unparalleled flexibility by combining high density, PDF417 and standard range bar code reading in one scan engine. The solid state scan engine delivers a snappy 200 scans per second, easily reading poor quality and damaged bar codes from up to 50 cm (19.7 inches) away.

Intermec's SF51 cordless scanner is designed for applications that require complete mobility and hands free scanning in transportation, logistics, warehousing and manufacturing environments. Used alone or coupled with an Intermec terminal or vehicle mount computer the SF51 excels in scan intensive applications such as picking, inventory management, direct store delivery, and work-in-process.

Intermec

**Physical Characteristics**

The SF51 is a small, industrial handheld scanner that fits comfortably into the user's hand, yet rugged enough to endure multiple drops and withstand harsh environments. The SF51 will connect wirelessly to a variety of fixed and mobile computer equipment using a low power Bluetooth™ radio link. The SF51 offers ease of configuration, simple one-button operation, long battery life, snappy decode performance, and general user friendliness.

**Warranty**

1 Year

**Physical Characteristics**

**Length:** 15.6cm (6.1 in.)

**Height:** 3.3cm (1.3 in.)

**Width:** 4.6cm (1.8 in.) in the front tapered to 3.2cm (1.26 in.) in the rear

**Weight:** 263gm (9.3 oz.)

**Power**

**Battery Type:** Lithium-ion

**Battery Life:** Scanning at 5 second intervals will last approx. 15 hours or 10,000 scans

**Recharging Time:** 3 hours

**Terminal Connectivity**

Intermec Bluetooth enabled terminals including 700 series, CK30, CK31, CK60, CV30, and CV60.

Will also connect to PC via USB or serial port using an Intermec RS232 or USB Bluetooth adapter.

**Scanning Performance of the EV10 Scan Engine**

**Scan rate:** 200 scans per second

**Minimum X dimension:** 4 mils (0.1mm)

**Scan Range:** up to 50cm

**Scan angles:** 40 degrees

**Print Contrast Ratio:** down to 25%

**Skew:** ±48°

**Pitch:** ±48°

**Light source:** 617nm Highly Visible LED

**Radio Characteristics**

**Frequency Band:** 2.4 Ghz

**Radio Type:** Bluetooth Class 1 version 1.2

**Radio Data Rate:** 1 megabit per second

**Range:**

**Host radio Class 1:** 30.5 meters (100 ft.)

**Host radio Class 2:** 10 meters (32.8 ft.)

**Features:** Adaptive Frequency Hopping (ADF)

**Accessories**

- Single bay charger
- Four bay charger
- Belt clip holder
- Industrial belt clip holder
- Forearm Holster
- Chest Strap Holder
- USB Bluetooth Adapter
- EasySet™ Configuration Utility

**Environment**

**Operating Temperature:**

-20°C to +50°C (-4°F to +122°F)

**Storage Temperature:**

-20°C to +60°C (-4°F to 140°F)

**Recharging Temperature:**

0°C to +35°C (32°F to +95°F)

**Humidity:** 0 - 95% RH, Non-condensing

**Shock and Vibration Protection:** SAE

Specification J1399 Class 3 (off road vehicle)

**Rain and Dust Resistance:** IP52 rated

**Drop Survival:** 26 drops onto concrete or steel surface from a height of 1.8 m (6 ft)

**Ambient light:** works in any lighting conditions from 0 to 100,000 lux

**Regulatory Approvals**

- UL/EN 60950 – Safety of Information Technology Equipment
- EN60825-1 – Safety of Laser Products (which also regulates LEDs)
- EN 55022 / CISPR22, Class B – Information Technology Equipment: Radio frequency disturbance characteristics
- Part 15 of FCC rules, Class B – Radio Frequency Devices
- US and Canadian UL (UL60950)
- TUV or GS (Germany) (EN60950, EN60825-1)
- NOM (Mexico) (NOM-019-SCFI-1998 based on IEC60950)
- C-TICK (Australia and New Zealand) (AS/NZS 3548 based on CISPR22)

**Scan Range**

| Bar Code Label Size | Scan Range                              |
|---------------------|---|
| 4 mil               | 11.9cm – 12.95cm<br>(4.7 in. - 5.1 in.) |
| 12 mil              | 4.57cm – 23.9cm<br>(1.8 in. - 9.4 in.)  |
| 20 mil              | 4.31cm – 30cm<br>(1.7 in. - 11.8 in.)   |
| 40 mil              | 11.9cm – 39.9cm<br>(4.7 in. - 15.7 in.) |
| 100% UPC/EAN        | 4.57cm – 23.9cm (1.8 in. - 9.4 in.)     |

**Bar Code Symbologies**

| Type    | Name                          |
|---------|-------------------------------|
| 1D      | Code 128/ EAN 128             |
| 1D      | Code 39                       |
| 1D      | Interleaved 2/5               |
| 1D      | UPC/EAN/ISBN<br>incl. add-ons |
| 1D      | 2/5 Matrix, standard          |
| 1D      | Codabar                       |
| 1D      | Code 93                       |
| 1D      | MSI                           |
| 1D      | Plessey                       |
| 1D      | Code 93i                      |
| 1D      | Code 11                       |
| 1D      | Telepen                       |
| 1D      | ISBT 128                      |
| 1D      | RSS                           |
| Stacked | RSS                           |
| Stacked | Micro PDF*                    |
| Stacked | PDF                           |
| Stacked | Macro PDF*                    |
| Stacked | Codablock                     |

\* Only on PDF enabled model

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**  
9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/  
Middle East & Africa  
Headquarters**

Reading International Business Park  
Basingstoke Road  
Reading RG2 6DD  
United Kingdom  
tel: 44.118.923.0800  
fax: 44.118.923.0801

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

**Beijing Representative Office**

29 FL, Unit A1, China Merchant Tower  
118 Jian Guo Road  
Chaoyang District, Beijing 100022  
Tel: 86.10.5165.5922  
Fax: 86.10.6567.6778

**Australia**

Level 4, 1-3 Atchison Street  
St. Leonards, NSW 2065  
Australia  
tel: 61.2.9330.4400  
fax: 61.2.9437.0204

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Samuel Morse 120 9 andar  
Brooklin CEP04576-060  
São Paulo, SP  
Brazil  
tel: 55.11.5502.6770

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.241.4800  
fax: 525.55.211.8121

**Internet**

www.intermec.com

**Sales**

800.934.3163  
(toll free in N.A.)  
tel: 425.348.2726

**OEM Sales**

tel: 425.348.2762

**Customer Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611541-01D 09/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





## BARCODING, WIRELESS AND DATA COLLECTION

*Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.*

*TPI will facilitate your entire wireless and data collection project:*

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

*TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.*

Product specification sheet provided by TPI

**www.tpi1.com**  
**888-488-4244**

