



Zebra® 105SL™

Thermal, On-Demand, All-Metal Bar
Code Printer

Serious about bar coding? Here's the choice of experience.

The 105SL combines enhanced memory, processing capacity, and features with rugged and reliable all-metal construction. Proven platform longevity plus fast processing and print speed make it the choice of experienced users who value reliability, productivity, consistent print quality, network compatibility, and superior service and support.

Cutting-Edge Network Connectivity

The 105SL offers flexible connectivity solutions including ZebraNet® Wireless Plus print server to free you to move or reconfigure the printer without costly recabling, plus ZebraNet 10/100 Print Server, which offers a complete wired solution when using 10Base-T, 100Base-TX, and fast Ethernet 10/100 auto-switching networks. And with Zebra advanced printer management, gain the efficiency and the ease of centralized monitoring and control of your Zebra printers and ZebraNet print servers.

The 105SL is ideal for moderate- to high-volume printing applications (including distributed, batch, or single format) in:

- Manufacturing and compliance labeling
- Logistics and inventory control
- Product identification marking
- Work in process



105SL



A tough steel housing, metal interior components, and an extruded metal printhead mechanism contribute to the 105SL's reliability in industrial environments.

STANDARD FEATURES

Print methods: Thermal transfer or direct thermal
Construction: Steel frame and cabinet with metal interior components
Multi-level Element Energy Equalizer™ (E³) for superior print quality
Fast 32-bit processing
Selectable print speeds up to 8"/second
Transmissive media sensor
Standard 2-line, 16-character LCD control panel
Internal Real-Time Clock

PRINTER SPECIFICATIONS

Resolution
203 dpi/8 dots per mm;
300 dpi/12 dots per mm (optional)

Memory
Standard: 6 MB SDRAM; 4 MB Flash
Optional: Up to 256 MB - PCMCIA card or CompactFlash) CompactFlash not supported with ZebraNet Wireless Plus
64 MB Flash memory (factory installed)

Print Width
Width: 4.09"/104 mm

Print Length with 203 dpi:
106"/2,692 mm (with standard memory)

Print Length with 300 dpi (optional):
65"/1,651 mm (with standard memory)

Print Speed
8"/203 mm per second (203/300 dpi)

Media Sensors
Transmissive (standard) and Reflective (optional)

*Specifications subject to change without notice. ©2006 ZIH Corp. ZebraDesigner, ZebraLink, ZebraNet, APL, Element Energy Equalizer, and all product names and numbers are Zebra trademarks and Zebra, ZebraNet, E³ and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Centronics is a registered trademark of Centronics Data Computer Corporation. CG Triumvirate is a trademark of Agfa Division, Miles Inc. IBM is a registered trademark of International Business Machines Corporation. UFST is a registered trademark of Monotype Imaging, Inc. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners.

Specifications at a Glance*

MEDIA CHARACTERISTICS

Maximum label and liner length
39"/991 mm

Maximum label and liner width
.79"/20 mm to 4.52"/115 mm

Maximum roll outer diameter (O.D.)
8"/203 mm

Core inner diameter (I.D.)
3"/76 mm

Media thickness
.003"/.076 mm to .012"/.305 mm

Media types
Roll-feed, die-cut, continuous, fanfold, tags, tickets
For optimum print quality and printer performance, use Genuine Zebra Supplies.

RIBBON CHARACTERISTICS

Outside diameter
3.2"/81.3 mm

Standard length
984'/300 m to 1,476'/450 m

Ratio
2:1 and 3:1 media roll to ribbon ratio

Width
.79"/20 mm to 4.5"/114 mm

Ribbon setup
Ribbon wound ink side out
Ribbon is recommended to be at least as wide as media.

Core inner diameter (I.D.)
1"/25.4 mm

OPERATING CHARACTERISTICS

Environmental
Operating Temp. 32° F/0° C to 104° F/40° C
Storage/Environ. -40° F/-40° C to 140° F/60° C
Operating Humidity 20-85% non-condensing
Storage Humidity 5-85% non-condensing

Electrical
Universal power supply with factor correction
90-264 VAC; 48-63 Hz

Agency Approvals
UL 1950; CISPR 22 (Class B); CSA 950; IEC 950;
801-2, -3 and -4 standards; Canadian Doc.
(Class A); FCC (Class A); CE compliance

PHYSICAL CHARACTERISTICS

Width: 11.2"/283 mm
Height: 15.5"/394 mm
Depth: 19.5"/495 mm
Weight: 55 lbs/25 kg
Shipping weight: 63 lbs./29 kg

RELATED PRODUCTS

Options and Accessories
300 dpi printhead
Full width cutter with orderable catch tray
Internal rewind spindle
Peel/liner rewind (for print-and-apply)
Reflective media sensor
Fanfold bin

ZEBRALINK™ SOLUTIONS

Software
ZebraDesigner™ Pro
ZebraNet™ Bridge Enterprise
ZebraNet Utilities v 7.0
Zebra Universal Driver
European and Asian font sets

Networking
ZebraNet 10/100 Print Server (internal or external)
ZebraNet Wireless Print Server
ZebraNet Wireless Plus
ZebraNet PrintServer II (internal or external)
Twinax and coax interfaces (internal)

Firmware
ZPL II®—Universal language for Zebra printers.
Simplifies label formatting and enables format compatibility with other Zebra printers.
Global Printing—Unicode™ compliant for fast multi-language, on-demand thermal printing right out of the box.
APL™—In many cases, Zebra's Alternate Programming Language allows integration of the 105SL printer into mixed printer environments without format re-programming (available in 203 dpi printers only). For additional information on Zebra's APL products please visit www.zebra.com.
Web View—Enables you to connect and control your bar code printer's Web interface using a common Web browser.
Alert—Printers equipped with ZebraNet print servers will notify you via any email-enabled, wired, or wireless device to minimize downtime.

COMMUNICATION AND INTERFACE CAPABILITIES

Centronics® RS-232 RS-422*, and RS-485* serial ports; IEEE 1284 bi-directional parallel

BAR CODE SYMBOLOGIES

Linear Bar Codes
Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, RSS

2-Dimensional
Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, RSS, Aztec

FONTS AND GRAPHICS

Fonts and Character Sets
Standard Fonts: 7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
Sets: IBM® Code Page 850 International character set
Contains UFST® from Monotype Imaging, Inc.

Graphic Features
Supports user-defined fonts and graphics—including custom logos
ZPL II drawing commands—including boxes, circles and diagonal lines



HEADQUARTERS Zebra Technologies International, LLC **T:** +1 847 793 2600 or +1 800 423 0442 **F:** +1 847 913 8766
ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

OTHER LOCATIONS **USA:** California, Rhode Island, Wisconsin **EUROPE:** France, Germany, Italy, Netherlands, Poland, Spain, Sweden, United Kingdom **ASIA-PACIFIC:** Australia, China, Japan, Singapore, South Korea
LATIN AMERICA: Florida (USA), Mexico **AFRICA/MIDDLE EAST:** South Africa, United Arab Emirates



An ISO 9001 registered company
GSA#: GS-35F-0268N
©2006 ZIH Corp. Printed in U.S.A.
#11341L Rev. 19 (9/06) 7.5M



BARCODING, WIRELESS AND DATA COLLECTION

Our customers turn to us to help them become more productive and profitable. TPI's expertise guarantees your project will be successful: on time, on budget and meet your ROI requirements.

TPI will facilitate your entire wireless and data collection project:

- ✓ *Business analysis*
- ✓ *Project justification & ROI*
- ✓ *Wireless design, RF site survey and spectrum analysis*
- ✓ *WWAN, WLAN design & installation*
- ✓ *Custom software*
- ✓ *Integration w/legacy systems*
- ✓ *Mobile computers*
- ✓ *Data collection terminals*
- ✓ *Barcode printers, labels and scanners*
- ✓ *RFID solutions*
- ✓ *Configuration and deployment*
- ✓ *Training and installation*
- ✓ *Service and upgrades*
- ✓ *Remote device management and support*

TPI can share best practices in data collection from a number of industries including wholesale distribution, manufacturing, healthcare and retail/consumer goods. Our expertise allows you to shorten your learning curve and increase your return on investment.

Product specification sheet provided by TPI

www.tpi1.com
888-488-4244

